

P500 INTERIOR/EXTERIOR STAIN BLOCKING PRIMER

CHARACTERISTICS:

- Assures uniform appearance of topcoats
- Fast drying
- Assures adhesion of the topcoat to slick, glossy surfaces such as glossy paints, varnished or lacquered woodwork
- Seals out solvent sensitive stains - tar, solvent based markers, etc. and minor dried water stains
- Performance alternate for Federal paint Specifications TT-P-650D and A-A 2994 Type II
- This product contains no Ethylene Glycol and no reportable amounts of Crystalline Silica.

Uses on interior:

Drywall, Cured Plaster, Ceiling Tiles, Paneling, PVC Piping, Wall Laminates

Uses on interior & exterior:

Galvanized metal, Aluminum, Wood, Hardboard, Previously Painted Surfaces

Color: White

Coverage: 400 sq. ft./gal @ 4 mils wet; 1.4 mils dry
Drying Time (At 77 °F, 50% RH, temperature and humidity dependent): To touch- 30 minutes; to recoat as a primer- 1 hour; to recoat as a stain sealer, 4 hours

Finish: Flat

Tinting: May tint to top-coat color. Check color before use

Vehicle Type: 100% Acrylic Latex

VOC: Does not exceed 200 g/L

APPLICATION

Apply at temperatures above 50 °F.

For stain blocking, use thin coats allowing ample (4 hr) drying time between coats.

Do not reduce for stain blocking.

No reduction necessary.

Brush - nylon/polyester

Roller - 1/4" - 3/4" nap synthetic roller cover.

Sprayer - Airless; Pressure - 2000 psi; Tip - .015" - .021"

SURFACE PREPARATION:

Remove all surface contamination by washing with a concentrated cleaner or other appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull.

Special recommendations - After priming stained areas, allow to dry 4 hours, test a small area for bleeding by applying the topcoat before painting the entire project. If the stain bleeds through, apply a second coat of primer and allow to dry overnight and retest before topcoating.

Fire restoration work - Thoroughly clean the surface before applying to smoke stained areas. Apply one or two coats of Teifs Interior/Exterior Stain Blocking Primer and test a small area for bleeding before painting the entire surface.

General Priming - Teifs Exterior Stain Blocking Primer can be topcoated in 1 hour on non-stain blocking applications.

Spot priming - a non-uniform appearance may result, due to differences in holdout between primed and unprimed areas. To avoid this, prime the entire surface rather than spot priming.

Plaster - Must be cured, usually 30 days and hard. Soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry before painting.

Wood - Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

Tile - Tile, laminate, ceramic and plastic tiles, and similar glossy surfaces, must be free of all oil, grease, and soap residue. DO NOT use this product in areas subject to excessive water, e.g.: in showers, around sinks, or on counter tops.

Caulking - Fill gaps between walls, ceilings, crown moldings, and other trim with a premium siliconized acrylic latex caulk after priming the surface.

Mildew - Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.

Testing - On hard, slick, glossy or otherwise hard to paint surfaces, after preparing the surface, apply a test area of this primer, allow to dry properly and test for adhesion.

CLEAN UP:

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTION:

- Protect from freezing
- Non-photochemical reactive
- Do not apply if surface temperature is below 50 °F.
- Close container after each use.

LABEL CAUTIONS:

CAUTION: Wear NIOSH approved respirator while working with this product. Use only with adequate ventilation. Open windows and doors or use other means to ensure fresh air entry during application and drying to avoid overexposure. If you experience dizziness, headaches or watering of eyes, leave the area. Avoid getting in eyes or on skin. Wash hands after using. Keep in original closed container after use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF CHILDREN.**

Surface Preparation Warning:

WARNING! If you scrape, sand, or remove OLD PAINT, you may release lead dust. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. LEAD IS TOXIC. Exposure to LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE,

ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to "http://www.epa.gov/opptintr/lead/index.html". You may also contact your local health authorities for information concerning prevention of lead exposure.

- Proper results will only be obtained if application conforms to Teifs Product Data Sheets, Specifications, Application and Installation Instructions. They are available on request at no charge.
- Consult Teifs Material Safety Data Sheet before using this product.
- Contact with eyes and/or prolonged contact with skin can be irritating. If such irritation occurs, flush immediately with water and see a physician.
- This product complies with all federal regulations concerning mercury and lead content.

The information and recommendations set forth in this product data sheet are based upon tests conducted by or on behalf of Teifs. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Teifs representative to obtain the most recent product data sheet.

TEIFS



PROFESSIONAL COATINGS

220 Burleson • San Antonio, Texas 78202
Tel: (210) 472-2935 • 1-800-358-4785
Fax: (210) 472-2946 • www.teifs.com

ParexLahabra Inc. Corporate Office
4125 E. La Palma Ave, Suite 250,
Anaheim, CA 92807
Phone: (714) 778-2266 Fax: (714) 774-2074

Product #316 1/07 © ParexLahabra

This information is designed to guide you and has been conscientiously compiled according to the latest state of our technology. No liability can be accepted in connection with the use of the product because of the great variety of applications and working conditions.