

P650 INTERIOR PRIMER SEALER

Characteristics:

P650 Interior Primer Sealer is a latex primer and general purpose sealer that prepares interior walls for a smooth and uniform finish coat. For new drywall, this sealer fills and surfaces the drywall and paper joints, evens the porosity and minimizes surface imperfections such as paper fuzz, minor sanding grooves, nicks and pinholes. It is also excellent as a cover coat for dramatic color changes.

Use - Interior Only: To be used on drywall, cured masonry, plaster and concrete and previously painted surfaces. Reduce with water if required.

- Color: white
- Coverage: 370 square feet per gallon; 4.3 mils wet; 1.0 mils dry.
- Drying Time: (77 °F; 50% RH): To touch 1 hour; recoat 4 hours.
- Tint: Use universal tints to approximate the finish coat color. Use up to 4 oz. per gallon of colorant.
- VOC: Does not exceed 100 g/L
- Solvent reducer: water
- This product contains no Ethylene Glycol and no reportable amounts of Crystalline Silica
- Performance alternate for Federal Paint Specification TTP-650D
- Meets MPI 50

Application:

P650 Primer Sealer can be used as a primer under latex flats, alkyd, latex enamels, water based epoxy or solvent based epoxy on interior architectural application. Do not apply at temperatures below 50 °F.

When topcoating with enamels, 2 topcoats are required for full sheen development, reducing the potential for areas of uneven sheen when touching up.

Brush: No reduction is necessary. Use a nylon, polyester brush.

Roller: No reduction is necessary. Use a 3/8" to 3/4" synthetic nap roller cover.

Airless Spray: Pressure: 2000 PSI; Tip: .017"-.021".

Clean Up:

Clean spills and spatters immediately with soap and water. Equipment and hands should be cleaned with soap and water. Equipment should be flushed with clean water and then refilled with mineral spirits to reduce rusting.

Caution:

- For interior use only.
- Protect from freezing.
- Non-photochemical reactive.

LABEL CAUTIONS:

CAUTION: Wear NIOSH approved respirator while working with this product. Use only with adequate ventilation. Open windows and doors or use other means to ensure fresh air entry during application and drying to avoid overexposure. If you experience dizziness, headache or watering of eyes, leave the area. Avoid getting in eyes or on skin. Wash hands after using. Keep in original closed container after use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY.

KEEP OUT OF THE REACH OF CHILDREN.

Surface Preparation Warning:

WARNING! If you scrape, sand, or remove OLD PAINT, you may release lead dust. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. LEAD IS TOXIC. Exposure to LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to "<http://www.epa.gov/opptintr/lead/index.html>". You may also contact your local health authorities for information concerning prevention of lead exposure.

- Proper results will only be obtained if application conforms to Teifs Product Data Sheets, Specifications, Application and Installation Instructions. They are available on request at no charge.
- Consult Teifs Material Safety Data Sheet before using this product.
- Contact with eyes and/or prolonged contact with skin can be irritating. If such irritation occurs, flush immediately with water and see a physician.
- This product complies with all federal regulations concerning mercury and lead content.

The information and recommendations set forth in this product data sheet are based upon tests conducted by or on behalf of Teifs. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Teifs representative to obtain the most recent product data sheet.

TEIFS



PROFESSIONAL COATINGS

220 Burluson • San Antonio, Texas • 78202
Tel: (210) 472-2935 • Fax: (210) 472-2946 • 1-800-358-4785
E-mail: teifs@teifs.com • www.teifs.com

ParexLahabra Inc. Corporate Office
4125 E. La Palma Ave, Suite 250, Anaheim, CA 92807
Phone: (714) 778-2266 Fax: (714) 774-2074

Product #331 - 1/07 © ParexLahabra

This information is designed to guide you and has been conscientiously compiled according to the latest state of our technology. No liability can be accepted in connection with the use of the product because of the great variety of applications and working conditions.