

# P710 TEIFSHIELD ALKALI RESISTANT PRIMER

## CHARACTERISTICS:

This product is designed to be applied as a barrier coat over stucco. The use of this product will seal the surface, provide a sound surface for succeeding coats and will minimize the formation of efflorescence as the stucco ages.

Color: White

Coverage: 400 sq. ft./gal @ 4 mils wet; 1.4 mils dry

Drying Time (At 77 °F, 50% RH, temperature and humidity dependent): To touch- 30 minutes; to recoat as a primer- 1 hour; to recoat as a stain sealer, 4 hours

Finish: Flat

Tinting: May tint to top-coat color. Check color before use.

Vehicle Type: 100% Acrylic Latex

VOC: Does not exceed 100 g/L

## APPLICATION:

Apply by brush, roller or airless spray. Thinning of this product is not recommended. If necessary, use only a small amount of clean water.

Apply at temperatures above 50 °F.

Brush - nylon/polyester

Roller - 1/2" - 3/4" nap synthetic roller cover

Sprayer - Airless; Pressure - 2000 psi; Tip - .015" - .021"

## CLEAN UP:

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

## CAUTION:

- Protect from freezing
- Non-photochemical reactive
- Do not apply if surface temperature is below 50 °F.
- Close container after each use.

## LABEL CAUTIONS:

CAUTION: Wear NIOSH approved respirator while working with this product. Use only with adequate ventilation. Open windows and doors or use other means to ensure fresh air entry during application and drying to avoid overexposure. If you experience dizziness, headaches or watering of eyes, leave the area. Avoid getting in eyes or on skin. Wash hands after using. Keep in original closed container after use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF THE REACH OF CHILDREN.**

## Surface Preparation Warning:

**WARNING!** If you scrape, sand, or remove OLD PAINT, you may release lead dust. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. LEAD IS TOXIC. Exposure to LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to "<http://www.epa.gov/opptintr/lead/index.html>". You may also contact your local health authorities for information concerning prevention of lead exposure.

- Proper results will only be obtained if application conforms to Teifs Product Data Sheets, Specifications, Application and Installation Instructions. They are available on request at no charge.
- Consult Teifs Material Safety Data Sheet before using this product.
- Contact with eyes and/or prolonged contact with skin can be irritating. If such irritation occurs, flush immediately with water and see a physician.
- This product complies with all federal regulations concerning mercury and lead content.

The information and recommendations set forth in this product data sheet are based upon tests conducted by or on behalf of Teifs. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Teifs representative to obtain the most recent product data sheet.

# TEIFS



PROFESSIONAL COATINGS

220 Bursleson • San Antonio, Texas • 78202  
Tel: (210) 472-2935 • Fax: (210) 472-2946 • 1-800-358-4785  
E-mail: [teifs@teifs.com](mailto:teifs@teifs.com) • [www.teifs.com](http://www.teifs.com)

ParexLahabra Inc. Corporate Office  
4125 E. La Palma Ave, Suite 250, Anaheim, CA 92807  
Phone: (714) 778-2266 Fax: (714) 774-2074

**Product #333 - 1/07 © ParexLahabra**

This information is designed to guide you and has been conscientiously compiled according to the latest state of our technology. No liability can be accepted in connection with the use of the product because of the great variety of applications and working conditions.