

P750 ACRYLIC BLOCK FILLER

Characteristics:

P750 is a premium quality, heavy duty 100% acrylic filler for filling interior or exterior open textured concrete block (CMU). May be used under variety of conventional topcoats and high performance coatings. This filler is not to be used as a waterproofer or used on walls where severe moisture or hydrostatic pressure may exist such as car washes, commercial kitchens, indoor swimming pool areas, or below grade basement walls.

- Excellent filling
- Excellent foundation for finish coats
- Excellent holdout
- Low odor
- Moisture and alkali resistant
- Accepts wide variety of topcoats
- Low VOC
- Performance alternate for Federal Specifications CID-A-A-1500 and TTF-1098D
- Formulated without ethylene glycol and contains no reportable quantities of crystalline silica.

Specifications:

- Color: White, tintable (limit 2 oz./gal.)
- Finish Flat
- Cleanup: Solvent soap and water
- VOC: Does not exceed 100 g/L
- Theoretical Coverage: 1.0 Mil Dry 722 sq. ft./gal
- Practical Coverage: apply @ 75-125 sq. ft./gal. on block walls and up to 100 sq. ft./gal. on relatively smooth masonry.
- Recommended film thickness: 8 mils dry - 16 mils wet
- Dry time: At 77 °F (25 °C) and 50% RH, dries to touch in 1 hour and to recoat overnight. Low temperature, high humidity, thick films or poor ventilation will increase these times.

Surface Preparation:

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, efflorescence, loose and flaking paint and other foreign substances.

Concrete Block

Cure mortar joints at least 30 days before filling blocks. pH must be 10.0 or lower. Do not use on cinder blocks containing slag, rust or iron.

Previously Painted Surfaces

Not recommended over old paints.

Tinting:

May be tinted with up to 2 oz/gal of colorants.

Application:

Mix thoroughly before use. May be applied by brush, roller or spray. No thinning required. Use a long nap roller for roll application or a tufted fiber masonry brush for brush application. Work material into the pores. For airless spray, a .033" orifice is recommended. Spray a full coat, back rolling immediately with a long nap roller. A roller is best to provide a textured surface. For full gloss development of gloss finishes, apply two coats of finish. Do not apply when surface or air temperature is below 50 °F (10 °C).

Clean Up:

Clean immediately with warm, soapy water.

Caution:

- Protect from freezing
- Non-photochemical reactive
- Do not apply if surface temperature is below 50 °F.
- Close container after each use.

LABEL CAUTIONS:

CAUTION: Wear NIOSH approved respirator while working with this product. Use only with adequate ventilation. Open windows and doors or use other means to ensure fresh air entry during application and drying to avoid

overexposure. If you experience dizziness, headaches or watering of eyes, leave the area. Avoid getting in eyes or on skin. Wash hands after using. Keep in original closed container after use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY.

KEEP OUT OF THE REACH OF CHILDREN.

Surface Preparation Warning:

WARNING! If you scrape, sand, or remove OLD PAINT, you may release lead dust. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. LEAD IS TOXIC. Exposure to LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to "<http://www.epa.gov/opptintr/lead/index.html>". You may also contact your local health authorities for information concerning prevention of lead exposure.

- Proper results will only be obtained if application conforms to Teifs Product Data Sheets, Specifications, Application and Installation Instructions. They are available on request at no charge.
- Consult Teifs Material Safety Data Sheet before using this product.
- Contact with eyes and/or prolonged contact with skin can be irritating. If such irritation occurs, flush immediately with water and see a physician.
- This product complies with all federal regulations concerning mercury and lead content.

The information and recommendations set forth in this product data sheet are based upon tests conducted by or on behalf of Teifs. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Teifs representative to obtain the most recent product data sheet.

TEIFS



PROFESSIONAL COATINGS

220 Burlleson • San Antonio, Texas • 78202
Tel: (210) 472-2935 • Fax: (210) 472-2946 • 1-800-358-4785
E-mail: teifs@teifs.com • www.teifs.com

ParexLahabra Inc. Corporate Office
4125 E. La Palma Ave, Suite 250, Anaheim, CA 92807
Phone: (714) 778-2266 Fax: (714) 774-2074

Product #324 - 1/07 © ParexLahabra

This information is designed to guide you and has been conscientiously compiled according to the latest state of our technology. No liability can be accepted in connection with the use of the product because of the great variety of applications and working conditions.