

PC1100 INTERIOR FLAT WALL

Characteristics:

Professional PC1100 is an interior, flat latex designed for the professional contractor to be used on walls and ceilings. This product can be used over primed plaster, sealed drywall, wood, masonry, and primed metal.

- Drying time: (77 °F, 50% RH): To touch 1 hour; recoat 4 hours.
- Coverage: 350-400 square feet at 4 mils wet; 1.25 mils dry.
- VOC: Does not exceed 50 g/L
- Provides performance, which is comparable to the products that are formulated in accordance with Federal specifications: TTP-29K and A-A-2246, Type I, II, Class I.

Specifications:

- Interior Galvanized Steel: 2 coats PC1100 Latex Flat Wall.
- Block: 1 coat Teifs P750 Acrylic Block Filler; 1 or 2 coats PC1100 Latex Flat Wall to meet coverage recommendations.
- Drywall: 1 coat Teifs P650 Primer Sealer; 1 or 2 coats PC1100 Latex Flat Wall to meet coverage recommendations.
- Plaster and Masonry: 1 coat Teifs P710 TeifShield; 1 or 2 coats PC1100 Latex Flat Wall to meet coverage recommendations.
- Primed Steel: 2 coats PC1100 Latex Flat Wall.
- New Wood: 1 coat P650 Primer Sealer; 1 or 2 coats PC1100 Latex Flat Wall to meet coverage recommendations.

Surface Preparation:

Galvanized Steel

Wipe all galvanized steel with commercial cleaning compound to remove any oil, grease, or other surface contaminations. Any corrosion observed must be removed with sand paper or steel wool.

Block, Masonry, Concrete and Plaster

All new surfaces must cure for at least 28 days. Make sure that all form release agents and curing membranes are removed. Block should be filled with Teifs T750 Acrylic Block Filler. Masonry, concrete and plaster must be primed with Teifs T710 TeifShield.

Primed Steel

If steel is clean and primer is not damaged, apply Teifs PC1100 Latex Flat Wall directly to steel. If primer has been damaged or if bare steel is observed, re-prime with P200 DTM Acrylic Primer/Finish.

New Wood

Make sure all dust and contamination has been removed from new wood. Patch all holes with a wood filler or putty and sand smooth.

Application:

Apply at temperatures above 50 °F. If reduction is required, use clean water, at a rate of 1-2 pints per 5 gallons.

Brush: Use a nylon/polyester brush.

Roller: Use a 3/8" - 3/4" nap synthetic roller cover.

Spray: Airless; Pressure: 2000 PSI; Tip: .017" - .021"

Clean Up:

Clean spills and splatters immediately with soap and water. Equipment and hands should be cleaned with soap and water. Equipment should be flushed with clean water and then reflushed with mineral spirits to reduce rusting.

Caution:

- For interior use only
- Protect from freezing
- Non-photochemical reactive

LABEL CAUTIONS:

CAUTION: Wear NIOSH approved respirator while working with this product. Use only with adequate ventilation. Open windows and doors or use other means to ensure fresh air entry during application and drying to avoid overexposure. If you experience dizziness, headache or watering of eyes, leave the area. Avoid getting in eyes or on skin. Wash hands after using. Keep in original closed container after use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF CHILDREN.**

Surface Preparation Warning:

WARNING! If you scrape, sand, or remove OLD PAINT, you may release lead dust. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. **LEAD IS TOXIC.** Exposure to **LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to "<http://www.epa.gov/opptintr/lead/index.html>". You may also contact your local health authorities for information concerning prevention of lead exposure.

- Proper results will only be obtained if application conforms to Teifs Product Data Sheets, Specifications, Application and Installation Instructions. They are available on request at no charge.
- Consult Teifs Material Safety Data Sheet before using this product.
- Contact with eyes and/or prolonged contact with skin can be irritating. If such irritation occurs, flush immediately with water and see a physician.
- This product complies with all federal regulations concerning mercury and lead content.

The information and recommendations set forth in this product data sheet are based upon tests conducted by or on behalf of Teifs. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Teifs representative to obtain the most recent product data sheet.

TEIFS



PROFESSIONAL COATINGS

TEIFS

220 Burseson • San Antonio, Texas • 78202
Tel: (210) 472-2935 • Fax: (210) 472-2946 • 1-800-358-4785
E-mail: teifs@teifs.com • www.teifs.com

ParexLahabra Inc. Corporate Office
4125 E. La Palma Ave, Suite 250, Anaheim, CA 92807
Phone: (714) 778-2266 Fax: (714) 774-2074

Product #335 - 1/07 © ParexLahabra

This information is designed to guide you and has been conscientiously compiled according to the latest state of our technology. No liability can be accepted in connection with the use of the product because of the great variety of applications and working conditions.