

# PC2000 EXTERIOR FLAT

## CHARACTERISTICS:

PC2000 Acrylic Latex House Paint is a flat, exterior, high quality, mildew resistant, 100% acrylic latex house paint designed for the professional contractor. This product is recommended for use on new primed or previously painted wood, masonry, hardwood, primed metal and weathered aluminum. PC2000 has excellent weathering and color retention, excellent blister and crack resistance, and is mildew resistant.

- Drying time: (77 °F, 50% RH); touch 30 minutes; recoat 4 hours.
- Coverage: 350 to 400 S.F. per gallon depending on method of application, texture and porosity of surface.
- Film thickness: 1.2 mils dry at 4.0 mils wet.
- Finish: Flat
- VOC: Does not exceed 100 g/L
- Thinning: This is not normally needed. If necessary, thin with up to 1/2 pint of water per gallon.
- The dry film of this product resists the growth of microbes on the surface.

## APPLICATION:

### New Surfaces

Wood: Prime new wood with Teifs P500 Stain Blocking Primer. On Redwood and Cedar, two coats may be required.

Unprimed Hardboard Siding: Prime entire surface including butt joints and drip edges with Teifs P500 Stain Blocking Primer. Caulk all joints, cracks and flashings.

Masonry and Stucco: Prime with P710 TeifShield Alkali Resistant Primer.

Ferrous Metal: Prime with Teifs P200 DTM Acrylic Primer Finish.

Galvanized Metal: Prime with Teifs P500 Stain Blocking Primer.

### Previously Painted Surfaces

Remove all dirt and chalk. Spot prime bare areas. Sand glossy areas and wipe clean. If old paint is in poor condition, prime with Teifs P500 Stain Blocking Primer. On old masonry and concrete, power wash to remove old peeling paint and chalk. Prime with Teifs P500 Stain Blocking Primer.

MILDEW: Mildew is a natural occurrence over which we have no control and although every effort is made to make these paints mildew resistant, TEIFS cannot be held responsible for the formation of fungus on the paint film. To remove mildew from surfaces prior to painting, scrub with a solution of one part household bleach to three parts water. Rinse thoroughly with clean water and allow to dry completely before painting.

### Clean Up:

Clean spills and splatters immediately with soap and water. Equipment and hands should be cleaned with soap and water. Equipment should be flushed with clean water and then reflushed with mineral spirits to reduce rusting.

### Caution:

- For exterior use only
- Protect from freezing
- Non-photochemical reactive
- Do not apply if surface temperature is below 50 °F.
- Close container after each use.

### LABEL CAUTIONS:

CAUTION: Wear NIOSH approved respirator while working with this product. Use only with adequate ventilation. Open windows and doors or use other means to ensure fresh air entry during application and drying to avoid overexposure. If you experience dizziness, headache or watering of eyes, leave the area. Avoid getting in eyes or on skin. Wash hands after using. Keep in original closed container after use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists. If swallowed, call

Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF THE REACH OF CHILDREN.**

### Surface Preparation Warning:

**WARNING!** If you scrape, sand, or remove OLD PAINT, you may release lead dust. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. LEAD IS TOXIC. Exposure to LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to <http://www.epa.gov/opptintr/lead/index.html>. You may also contact your local health authorities for information concerning prevention of lead exposure.

- Proper results will only be obtained if application conforms to Teifs Product Data Sheets, Specifications, Application and Installation Instructions. They are available on request at no charge.
- Consult Teifs Material Safety Data Sheet before using this product.
- Contact with eyes and/or prolonged contact with skin can be irritating. If such irritation occurs, flush immediately with water and see a physician.
- This product complies with all federal regulations concerning mercury and lead content.

The information and recommendations set forth in this product data sheet are based upon tests conducted by or on behalf of Teifs. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Teifs representative to obtain the most recent product data sheet.

# TEIFS



PROFESSIONAL COATINGS

220 Burlison • San Antonio, Texas • 78202  
Tel: (210) 472-2935 • Fax: (210) 472-2946 • 1-800-358-4785  
E-mail: [teifs@teifs.com](mailto:teifs@teifs.com) • [www.teifs.com](http://www.teifs.com)

ParexLahabra Inc. Corporate Office  
4125 E. La Palma Ave, Suite 250, Anaheim, CA 92807  
Phone: (714) 778-2266 Fax: (714) 774-2074

**Product #339 - 1/07 © ParexLahabra**

This information is designed to guide you and has been conscientiously compiled according to the latest state of our technology. No liability can be accepted in connection with the use of the product because of the great variety of applications and working conditions.