



Venetian Plaster Matte

DESCRIPTION:

Venetian Plaster Matte is an interior and exterior acrylic plaster made with the highest quality ingredients. It is a unique decorative and protective coating designed for matte/flat faux finishing. It is easy and quickly applied to walls, columns, and ceilings. Venetian Plaster Matte provides dramatic high quality finish results and nearly endless design applications. It can simulate the visual effect of old world marble and old world plaster with near infinite color variations.

USES:

Use Venetian Plaster Matte Base as a basecoat for Venetian Plaster Matte to create a faux finish, old world marble or an old world plaster look.

COMPOSITION:

- Binder base: 100% acrylic polymer.
- Water-based: VOC- compliant.
- Pigment base: Titanium dioxide.

PROPERTIES:

- A finishing product that is easy to use.
- Versatility of designs beyond compare.
- Near infinite color selections to complement existing interiors.
- Elegant and sophisticated interior theme.

CONTAINER:

55 lbs (24.9 kg) net weight in 5 gal plastic pails

- One gallon (3.9 L) can
- One quart (0.95 L) can
- Storage: Protect from direct sunlight and freezing at all times.
- Do not stack pails more than 3 pails high
- Shelf Life: One year if properly stored in original unopened container.

COVERAGE:

Coverage will vary depending on surface conditions, thickness and number of applications.

- Venetian Plaster Matte:
Approximately 240–300 sq. ft. per gallon

SURFACE PREPARATION:

Exterior Directions:

Surfaces must be clean, dry, structurally sound and free from efflorescence, grease, oil, form release agents and curing compounds. Apply Venetian Plaster Matte Base according to the Venetian Plaster Matte Base directions.

Interior Directions:

Interior gypsum board should be finished to a Level 3 finish. For previously painted surfaces, all loose and chalking paint must be removed, and glossy surfaces dulled. Surfaces should be primed with a color matched acrylic primer. Never install on rough or uneven substrates.

MIXING:

Read the entire label before using this product.

1. Use clean equipment for mixing and preparation.
2. Stir to obtain a homogeneous consistency using a heavy-duty 1/2-in. (13mm) drill with a rust free paddle at 400–500 rpm. Avoid air entrainment.

APPLICATION:

Parex USA recommends that the project owner or designer approve a job site mock-up of the application of this product. The mock-up should demonstrate the products' appearance under the conditions given by the project specification(s).

1. Apply Venetian Plaster Matte using a small chrome steel trowel or stainless drywall tapping knife in small random-multidirectional overlapping strokes-back troweling each stroke immediately pulling it down tight, skimming the wall with a very thin coat. Allow the material to dry completely prior to any further applications or being exposed to moisture.
2. Apply the second coat in the same manner to the first and allow to dry completely.

CLEAN-UP

Clean tools frequently using clean water prior to drying.

LIMITATIONS:

- Do not apply Venetian Plaster Matte to create significant texture.
- Applying Venetian Plaster Matte too thick will result in crazing, checking, curling and or peeling.
- Use only on surfaces that are sound, clean, dry, and free from any residue that might affect the ability of this product to bond to the surface.
- Ambient and surface temperature must be 40°F (4.4°C) or higher during application and drying time. Provide supplemental heat and protection from moisture as needed.
- Application in direct sunlight in hot weather may adversely affect aesthetics.
- Do not allow to freeze until completely dry.
- Do not use harsh or abrasive cleaners. Venetian Plaster Matte can be washed using a soap and water solution, followed by a warm water rinse. Use a soft bristle brush for cleaning.

WARNING:

- Read complete Warning information printed on product container prior to use. For medical emergency information, call 1-800-424-9300.
- Always wear proper safety equipment, including particle mask, eye protection and gloves when mixing and/or applying this product.
- In case of contact with eyes, flush with clean water and seek medical attention if irritation persists.
- For more information on handling this product refer to its Material Safety Data Sheet (MSDS). The most current MSDS and Product Data Sheet (PDS) can be found on our website.
- This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Parex USA, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

PAREXUSA
www.parexusa.com

Corporate Office

Parex USA, Inc.
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
(866) 516-0061
Tech Support: (800) 226-2424

Facilities

Redan, GA
Riverside, CA
French Camp, CA
Colorado Springs, CO
Albuquerque, NM
San Antonio, TX
Wilkes Barre, PA
Ft. Pierce, FL

